

2. Product specifications

2-1. Feature & Specifications

Model	LN40B530P7N	
Feature		
▶ Digital-TV, RF, 3-HDMI, 1-Component, 1-A/V, 1-USB2.0, D-SUB ▶ Brightness : 500cd/m² ▶ High Contrast Ratio : 5000:1 ▶ Response Time : 6.5ms		
Specifications		
Item	Description	
LCD Panel	40inch FHD 60Hz	
Scanning Frequency	Horizontal : 60 kHz ~ 73 kHz (Automatic) Vertical : 47 Hz ~ 63 Hz (Automatic)	
Display Colors	16.7M color	
Maximum resolution	Horizontal : 1920 Pixels Vertical : 1080 pixels	
Input Signal	Analog 0.7 Vp-p ± 5% positive at 75Ω , internally terminated	
Input Sync Signal	H/V Separate, TTL, P. or N.	
Maximum Pixel Clock rate	80MHz	
Active Display Horizontal/Vertical	35.11 x 19.85 inches (891.7 (H) x 504.2 (V) mm)	
AC power voltage & Frequency	AC 110V ~ 220V, 60 Hz	
Power Consumption	Under 190W (Under 1W , Stand by)	
Dimensions Set (W x D x H)	39.3 x 10.2 x 27.0 inches (998.0 x 260.1 x 686.0 mm)_with stand 39.3 x 3.1 x 24.4 inches (998.0 x 78.4 x 620.8 mm)_without stand	
Weight	39.68 lbs (18.0kg)_with stand 33.29 lbs (15.1kg)_without stand	
TV System	Tunning	Frequency Synthesize (Refer to detailed Frequency Table)
	System	ATSC, NTSC5.38
	Sound	NTSC-M, AC-3 Digital
Environmental Considerations	Operating Temperature : 50°F ~ 104°F (10°C ~ 40°C) Operating Humidity : 10% ~ 80%, non-condensing Storage temperature : -13°F ~ 113°F (-25°C ~ 45°C) Storage Humidity : 5% ~ 95%, non-condensing	
Audio Spec.	- MAX Internal Audio Output Power : Each 10W(Left/Right) - Equalizer : 5band - Output Frequency : RF : 20 Hz ~ 15.4 kHz AV/Componet/HDMI : 20 Hz ~ 20 kHz	
Note: TruSurround HD, Game Mode, Film Mode, Energy Saving, Anynet+		

Model	LN46B530P7N	
Feature		
▶ Digital-TV, RF, 3-HDMI, 1-Component, 1-A/V, 1-USB2.0, D-SUB ▶ Brightness : 500cd/m² ▶ High Contrast Ratio : 5000:1 ▶ Response Time : 6.5ms		
Specifications		
Item	Description	
LCD Panel	46inch FHD 60Hz	
Scanning Frequency	Horizontal : 60 kHz ~ 73 kHz (Automatic) Vertical : 47 Hz ~ 63 Hz (Automatic)	
Display Colors	16.7M color	
Maximum resolution	Horizontal : 1920 Pixels Vertical : 1080 pixels	
Input Signal	Analog 0.7 Vp-p ± 5% positive at 75Ω , internally terminated	
Input Sync Signal	H/V Separate, TTL, P. or N.	
Maximum Pixel Clock rate	82MHz	
Active Display Horizontal/Vertical	40.08 x 22.55 inches (1018.08 (H) x 572.67 (V) mm)	
AC power voltage & Frequency	AC 110V ~ 220V, 60 Hz	
Power Consumption	Under 230W (Under 1W , Stand by)	
Dimensions Set (W x D x H)	44.4 x 10.2 x 30.2 inches (1127.0 x 260.0 x 766.0 mm)_with stand 44.4 x 3.1 x 28.0 inches (1127.0 x 77.8 x 712.1 mm)_without stand	
Weight	52.25 lbs (23.7kg)_with stand 43.65 lbs (19.8kg)_without stand	
TV System	Tunning	Frequency Synthesize (Refer to detailed Frequency Table)
	System	ATSC, NTSC5.38
	Sound	NTSC-M, AC-3 Digital
Environmental Considerations	Operating Temperature : 50°F ~ 104°F (10°C ~ 40°C) Operating Humidity : 10% ~ 80%, non-condensing Storage temperature : -13°F ~ 113°F (-25°C ~ 45°C) Storage Humidity : 5% ~ 95%, non-condensing	
Audio Spec.	- MAX Internal Audio Output Power : Each 10W(Left/Right) - Equalizer : 5band - Output Frequency : RF : 20 Hz ~ 15.4 kHz AV/Componet/HDMI : 20 Hz ~ 20 kHz	
Note: TruSurround HD, Game Mode, Film Mode, Energy Saving, Anynet+		

CHANNEL FREQUENCY TABLE

1. OUTPUT FREQUENCY : ANALOG fv:45.75MHz, fs:41.25MHz DIGITAL Fc:44MHz

2. TUNING STEP SIZE : FIRST PLL 250KHz SECOND PLL 62.5KHz

OSD	CH NO	AIR		BAND	CH NO	Cable STD		BAND	CH NO	Cable HRC		CH NO	Cable IRC	
		Air-DTV	Air-NTSC											
1	1								A-8	72.00		A-8	73.25	
2	2	57	55.25	V-L	2	55.25		V-L	2	54.00		2	55.25	
3	3	63	61.25	V-L	3	61.25		V-L	3	60.00		3	61.25	
4	4	69	67.25	V-L	4	67.25		V-L	4	66.00		4	67.25	
5	5	79	77.25	V-L	5	77.25		V-L	A-7	78.00		A-7	79.25	
6	6	85	83.25	V-L	6	83.25		V-L	A-6	84.00		A-6	85.25	
7	7	177	175.25	V-H	7	175.25		V-H	7	174.00		7	175.25	
8	8	183	181.25	V-H	8	181.25		V-H	8	180.00		8	181.25	
9	9	189	187.25	V-H	9	187.25		V-H	9	186.00		9	187.25	
10	10	195	193.25	V-H	10	193.25		V-H	10	192.00		10	193.25	
11	11	201	199.25	V-H	11	199.25		V-H	11	198.00		11	199.25	
12	12	207	205.25	V-H	12	205.25		V-H	12	204.00		12	205.25	
13	13	213	211.25	V-H	13	211.25		V-H	13	210.00		13	211.25	
14	14	473	471.25	UHF	A	121.25		MID	A	120.00		A	121.25	
15	15	479	477.25	UHF	B	127.25		MID	B	126.00		B	127.25	
16	16	485	483.25	UHF	C	133.25		MID	C	132.00		C	133.25	
17	17	491	489.25	UHF	D	139.25		MID	D	138.00		D	139.25	
18	18	497	495.25	UHF	E	145.25		MID	E	144.00		E	145.25	
19	19	503	501.25	UHF	F	151.25		MID	F	150.00		F	151.25	
20	20	509	507.25	UHF	G	157.25		MID	G	156.00		G	157.25	
21	21	515	513.25	UHF	H	163.25		MID	H	162.00		H	163.25	
22	22	521	519.25	UHF	I	169.25		MID	I	168.00		I	169.25	
23	23	527	525.25	UHF	J	175.25		SUPER	J	174.00		J	175.25	
24	24	533	531.25	UHF	K	181.25		SUPER	K	180.00		K	181.25	
25	25	539	537.25	UHF	L	187.25		SUPER	L	186.00		L	187.25	
26	26	545	543.25	UHF	M	193.25		SUPER	M	192.00		M	193.25	
27	27	551	549.25	UHF	N	199.25		SUPER	N	198.00		N	199.25	
28	28	557	555.25	UHF	O	205.25		SUPER	O	204.00		O	205.25	
29	29	563	561.25	UHF	P	211.25		SUPER	P	210.00		P	211.25	
30	30	569	567.25	UHF	Q	217.25		SUPER	Q	216.00		Q	217.25	
31	31	575	573.25	UHF	R	223.25		SUPER	R	222.00		R	223.25	
32	32	581	579.25	UHF	S	229.25		SUPER	S	228.00		S	229.25	
33	33	587	585.25	UHF	T	235.25		SUPER	T	234.00		T	235.25	
34	34	593	591.25	UHF	U	241.25		SUPER	U	240.00		U	241.25	
35	35	599	597.25	UHF	V	247.25		SUPER	V	246.00		V	247.25	
36	36	605	603.25	UHF	W	253.25		SUPER	W	252.00		W	253.25	
37	37	611	609.25	UHF	AA	259.25		HYPER	AA	258.00		AA	259.25	
38	38	617	615.25	UHF	BB	265.25		HYPER	BB	264.00		BB	265.25	
39	39	623	621.25	UHF	CC	271.25		HYPER	CC	270.00		CC	271.25	
40	40	629	627.25	UHF	DD	277.25		HYPER	DD	276.00		DD	277.25	
41	41	635	633.25	UHF	EE	283.25		HYPER	EE	282.00		EE	283.25	
42	42	641	639.25	UHF	FF	289.25		HYPER	FF	288.00		FF	289.25	
43	43	647	645.25	UHF	GG	295.25		HYPER	GG	294.00		GG	295.25	
44	44	653	651.25	UHF	HH	301.25		HYPER	HH	300.00		HH	301.25	
45	45	659	657.25	UHF	II	307.25		HYPER	II	306.00		II	307.25	
46	46	665	663.25	UHF	JJ	313.25		HYPER	JJ	312.00		JJ	313.25	
47	47	671	669.25	UHF	KK	319.25		HYPER	KK	318.00		KK	319.25	
48	48	677	675.25	UHF	LL	325.25		HYPER	LL	324.00		LL	325.25	
49	49	683	681.25	UHF	MM	331.25		HYPER	MM	330.00		MM	331.25	
50	50	689	687.25	UHF	NN	337.25		HYPER	NN	336.00		NN	337.25	
51	51	695	693.25	UHF	OO	343.25		HYPER	OO	342.00		OO	343.25	
52	52	701	699.25	UHF	PP	349.25		HYPER	PP	348.00		PP	349.25	
53	53	707	705.25	UHF	QQ	355.25		HYPER	QQ	354.00		QQ	355.25	
54	54	713	711.25	UHF	RR	361.25		HYPER	RR	360.00		RR	361.25	
55	55	719	717.25	UHF	SS	367.25		HYPER	SS	366.00		SS	367.25	
56	56	725	723.25	UHF	TT	373.25		HYPER	TT	372.00		TT	723.25	
57	57	731	729.25	UHF	UU	379.25		HYPER	UU	378.00		UU	729.25	
58	58	737	735.25	UHF	VV	385.25		HYPER	VV	384.00		VV	735.25	
59	59	743	741.25	UHF	WW	391.25		HYPER	WW	390.00		WW	741.25	
60	60	749	747.25	UHF	XX	397.25		HYPER	XX	396.00		XX	747.25	
61	61	755	753.25	UHF	YY	403.25		HYPER	YY	402.00		YY	753.25	
62	62	761	759.25	UHF	ZZ	409.25		HYPER	ZZ	408.00		ZZ	759.25	
63	63	767	765.25	UHF	AAA	415.25		HYPER	AAA	414.00		AAA	765.25	
64	64	773	771.25	UHF	BBB	421.25		HYPER	BBB	420.00		BBB	771.25	
65	65	779	777.25	UHF	CCC	427.25		ULTRA	CCC	426.00		CCC	777.25	
66	66	785	783.25	UHF	DDD	433.25		ULTRA	DDD	432.00		DDD	783.25	
67	67	791	789.25	UHF	EEE	439.25		ULTRA	EEE	438.00		EEE	789.25	
68	68	797	795.25	UHF	FFF	445.25		ULTRA	FFF	444.00		FFF	795.25	
69	69	803	801.25	UHF	GGG	451.25		ULTRA	GGG	450.00		GGG	801.25	


2. Product specifications

OSD	CH NO	AIR		BAND	CH NO	Cable STD	BAND	CH NO	Cable HRC	CH NO	Cable IRC
		Air-DTV	Air-NTSC								
70	70				HHH	499.25	ULTRA	HHH	498.00	HHH	499.25
71	71				III	505.25	ULTRA	III	504.00	III	505.25
72	72				JJJ	511.25	ULTRA	JJJ	510.00	JJJ	511.25
73	73				KKK	517.25	ULTRA	KKK	516.00	KKK	517.25
74	74				LLL	523.25	ULTRA	LLL	522.00	LLL	523.25
75	75				MMM	529.25	ULTRA	MMM	528.00	MMM	529.25
76	76				NNN	535.25	ULTRA	NNN	534.00	NNN	535.25
77	77				000	541.25	ULTRA	000	540.00	000	541.25
78	78				PPP	547.25	ULTRA	PPP	546.00	PPP	547.25
79	79				79	553.25	ULTRA	79	552.00	79	553.25
80	80				80	559.25	ULTRA	80	558.00	80	559.25
81	81				81	565.25	ULTRA	81	564.00	81	565.25
82	82				82	571.25	ULTRA	82	570.00	82	571.25
83	83				83	577.25	ULTRA	83	576.00	83	577.25
84	84				84	583.25	ULTRA	84	582.00	84	583.25
85	85				85	589.25	ULTRA	85	588.00	85	589.25
86	86				86	595.25	ULTRA	86	594.00	86	595.25
87	87				87	601.25	ULTRA	87	600.00	87	601.25
88	88				88	607.25	ULTRA	88	606.00	88	607.25
89	89				89	613.25	ULTRA	89	612.00	89	613.25
90	90				90	619.25	ULTRA	90	618.00	90	619.25
91	91				91	625.25	ULTRA	91	624.00	91	625.25
92	92				92	631.25	ULTRA	92	630.00	92	631.25
93	93				93	637.25	ULTRA	93	636.00	93	637.25
94	94				94	643.25	ULTRA	94	642.00	94	643.25
95	95				A-5	91.25	FM	A-5	90.00	A-5	91.25
96	96				A-4	97.25	FM	A-4	96.00	A-4	97.25
97	97				A-3	103.25	FM	A-3	102.00	A-3	103.25
98	98				A-2	109.25	MID	A-2	108.00	A-2	109.25
99	99				A-1	115.25	MID	A-1	114.00	A-1	115.25
100	100				100	649.25	ULTRA	100	648.00	100	649.25
101	101				101	655.25	ULTRA	101	654.00	101	655.25
102	102				102	661.25	ULTRA	102	660.00	102	661.25
103	103				103	667.25	ULTRA	103	666.00	103	667.25
104	104				104	673.25	ULTRA	104	672.00	104	673.25
105	105				105	679.25	ULTRA	105	678.00	105	679.25
106	106				106	685.25	ULTRA	106	684.00	106	685.25
107	107				107	691.25	ULTRA	107	690.00	107	691.25
108	108				108	697.25	ULTRA	108	696.00	108	697.25
109	109				109	703.25	ULTRA	109	702.00	109	703.25
110	110				110	709.25	ULTRA	110	708.00	110	709.25
111	111				111	715.25	ULTRA	111	714.00	111	715.25
112	112				112	721.25	ULTRA	112	720.00	112	721.25
113	113				113	727.25	ULTRA	113	726.00	113	727.25
114	114				114	733.25	ULTRA	114	732.00	114	733.25
115	115				115	739.25	ULTRA	115	738.00	115	739.25
116	116				116	745.25	ULTRA	116	744.00	116	745.25
.	.				.	.	.	.	.	.	.
.	.				.	.	.	.	.	.	.
125	125				125	799.25	ULTRA	125	798.00	125	799.25
.	.				.	.	.	.	.	.	.
.	.				.	.	.	.	.	.	.

2-2. New Features explanation


- Anynet+: Anynet+ is an AV network system that enables you to control all connected Samsung AV devices with the TV's remote.

To directly connect to TV



Connect the [HDMI 1], [HDMI 2] or [HDMI] jack on the TV and the HDMI OUT jack of the corresponding Anynet+ device using an HDMI cable.

To connect to Home Theater



1. Connect the [HDMI 1], [HDMI 2] or [HDMI] jack on the TV and the HDMI OUT jack of the corresponding Anynet+ device using an HDMI cable.
2. Connect the HDMI IN jack of the home theater and the HDMI OUT jack of the corresponding Anynet+ device using the HDMI cable.





- Connect the Optical cable between [Digital Audio Out (Optical)] on your TV and Digital Audio Input on the Home Theater.
- When following the connection above, the Optical jack only outputs 2 channel audio. You will only hear sound from the Home Theater's Front Left and Right speakers and the subwoofer. If you want to hear 5.1 channel audi connect the DIGITAL AUDIO OUT (OPTICAL) jack on the DVD / Satellite Box (ie Anynet Device 1 or 2) directly to the Amplifi er or Home Theater, not the TV.
- Connect only one Home Theater.
- You can connect an Anynet+ device using the HDMI 1.3 cable. Some HDMI cables may not support Anynet+ functions.
- Anynet+ works when the AV device supporting Anynet+ is in the Standby or On status.
- Anynet+ supports up to 12 AV devices in total. Note that you can connect up to 3 devices of the same type.

2-3. Specification Comparison to Old Models

※ O : application, X : non-application

Model	LB5P(LN**B530P7NXZA)		Pearl(LN**A530P1FXZA)	
Design				
Display Type	LCD TV		LCD TV	
Built-in Tuner	O		O	
Resolution	1920 x 1080		1920 x 1080	
LCD Panel	TFT LCD Panel 60Hz		TFT LCD Panel 60Hz	
Screen Size	40"/46"		40"/46"	
Picture ratio	16 : 9		16 : 9	
Dimensions (W x H x D)	40	39.3 x 27.0 x 10.2 inchs_with stand	40	41.7 x 26.5 x 9.5 inchs_with stand
	46	44.4 x 30.2 x 10.2 inchs_with stand	46	46.7 x 10.2 x 29.5 inchs_with stand
Weight	40	39.68 lbs_with stand	40	42.55 lbs_with stand
	46	52.25 lbs_with stand	46	58.64 lbs_with stand
Brightness	500 cd ²		500 cd ²	
Contrast Ratio	5000:1		5000:1	
Picture Enhacer	DNle (Saturn4)		DNle (FBE3)	
Equalizer	5 Band		5 Band	
Auto Volume Control	O		O	
Surround Sound	SRS TruSurround HD		SRS TruSurround XT	
Speaker Output	10W + 10W		10W + 10W	
PIP	X		O	
Double Window	X		O	
Caption	O		O	
Entertainment Mode	X		O	
Game Mode	O		X	
Energy Saving	O		O	
Anynet+	O		O	
Antenna	1(Cable/Air)		1(Cable/Air)	

2-4. Accessories

Product	Description	Code. No	Remark
	Remote Control & Batteries (AAA x 2)	BN59-00856A	Samsung Electronics Service center
	Power Cord	3903-000144	
	Cover-Bottom	40": BN63-05330A 46": BN63-05332A	
	Stand	40" : BN96-11165A 46" : BN96-11166A	
	Screw (for the stand - M4, L6)	6002-001294	
	Owner's Instructions	BN68-01883P	
	Cleaning Cloth	BN-63-01798B	
	Warranty Card / Registration Card / Safety Guide Manual (Not available in all locations)	AA68-03242L	
	TV-Holder & Screw (M4 X 16)	BN96-10788A	